

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An ink jet printhead comprising:
a plurality of nozzles each defining a planar ejection aperture; and
~~at least one a plurality of~~ respective heater element elements corresponding to each nozzle,
each heater element is in the form of a suspended beam having a planar structure suspended
between corresponding electrodes and extending in a plane parallel to that of the ejection
aperture; wherein
each heater element is arranged for being in thermal contact with a bubble forming
liquid,
each heater element is configured to heat at least part of the bubble forming liquid to
a temperature above its boiling point to form a gas bubble therein thereby to cause
the ejection of a drop of an ejectable liquid through the nozzle corresponding to that
heater element, ~~and~~
each heater element has two opposite sides parallel to the plane of the ejection
aperture and is configured such that a gas bubble formed by that heater element is
formed at both of said sides, and
the heater elements and associated electrodes are arranged in each nozzle so that the
electrodes are non-coincident.
2. (Original) The printhead of claim 1 being configured to support the bubble forming
liquid in thermal contact with each said heater element, and to support the ejectable liquid
adjacent each nozzle.
3. (Original) The printhead of claim 1 wherein the bubble forming liquid and the
ejectable liquid are of a common body of liquid.
4. (Original) The printhead of claim 1 being configured to print on a page and to be a
page-width printhead.

5. (Currently Amended) The printhead of claim 1 wherein each ~~heater element is in the form of a~~ suspended beam is configured such that a gas bubble formed by that heater element is formed so as to surround that heater element.
6. (Cancelled)
7. (Original) The printhead of claim 1 wherein each heater element is configured such that an actuation energy of less than 500 nanojoules (nJ) is required to be applied to that heater element to heat that heater element sufficiently to form a said bubble in the bubble forming liquid thereby to cause the ejection of a said drop.
8. (Original) The printhead of claim 1 configured to receive a supply of the ejectable liquid at an ambient temperature, wherein each heater element is configured such that the energy required to be applied thereto to heat said part to cause the ejection of a said drop is less than the energy required to heat a volume of said ejectable liquid equal to the volume of the said drop, from a temperature equal to said ambient temperature to said boiling point.
9. (Original) The printhead of claim 1 comprising a substrate having a substrate surface, wherein each nozzle has a nozzle aperture opening through the substrate surface, and wherein the areal density of the nozzles relative to the substrate surface exceeds 10,000 nozzles per square cm of substrate surface.
10. (Original) The printhead of claim 1 wherein the bubble which each heater element is configured to form is collapsible and has a point of collapse, and wherein each heater element is configured such that the point of collapse of a bubble formed thereby is spaced from that heater element.
11. (Original) The printhead of claim 1 comprising a structure that is formed by chemical vapor deposition (CVD), the nozzles being incorporated on the structure.
12. (Original) The printhead of claim 1 comprising a structure that is less than 10 microns thick, the nozzles being incorporated on the structure.

13. (Original) The printhead of claim 1 comprising a plurality of nozzle chambers, each corresponding to a respective nozzle, and a plurality of said heater elements being disposed within each chamber, the heater elements within each chamber being formed on different respective layers to one another.

14. (Original) The printhead of claim 1 wherein each heater element is formed of solid material more than 90% of which, by atomic proportion, is constituted by at least one periodic element having an atomic number below 50.

15. (Original) The printhead of claim 1 wherein each heater element includes solid material and is configured for a mass of less than 10 nanograms of the solid material of that heater element to be heated to a temperature above said boiling point thereby to heat said part of the bubble forming liquid to a temperature above said boiling point to cause the ejection of a said drop.

16. (Original) The printhead of claim 1 wherein each heater element is substantially covered by a conformal protective coating, the coating of each heater element having been applied substantially to all sides of the heater element simultaneously such that the coating is seamless.

17. (Currently Amended) A printer system incorporating a printhead, the printhead comprising:

a plurality of nozzles each defining a planar ejection aperture; and

~~at least one a plurality of~~ respective heater ~~element elements~~ corresponding to each nozzle, each heater element is in the form of a suspended beam having a planar structure suspended between corresponding electrodes and extending in a plane parallel to that of the ejection aperture; wherein

each heater element is arranged for being in thermal contact with a bubble forming liquid,

each heater element is configured to heat at least part of the bubble forming liquid to a temperature above its boiling point to form a gas bubble therein thereby to cause the ejection of a drop of an ejectable liquid through the nozzle corresponding to that heater element, ~~and~~

each heater element has two opposite sides parallel to the plane of the ejection aperture and is configured such that a gas bubble formed by that heater element is formed at both of said sides, and

the heater elements and associated electrodes are arranged in each nozzle so that the electrodes are non-coincident.

18. (Original) The system of claim 17 being configured to support the bubble forming liquid in thermal contact with each said heater element, and to support the ejectable liquid adjacent each nozzle.

19. (Original) The system of claim 17 wherein the bubble forming liquid and the ejectable liquid are of a common body of liquid.

20. (Original) The system of claim 17 being configured to print on a page and to be a page-width printhead.

21. (Currently Amended) The system of claim 17 wherein each ~~heater element is in the form of a~~ suspended beam is configured such that a gas bubble formed by that heater element is formed so as to surround that heater element.

22. (Cancelled)

23. (Original) The system of claim 17 wherein each heater element is configured such that an actuation energy of less than 500 nanojoules (nJ) is required to be applied to that heater element to heat that heater element sufficiently to form a said bubble in the bubble forming liquid thereby to cause the ejection of a said drop.

24. (Original) The system of claim 17, wherein the printhead is configured to receive a supply of the ejectable liquid at an ambient temperature, and wherein each heater element is configured such that the energy required to be applied thereto to heat said part to cause the ejection of a said drop is less than the energy required to heat a volume of said ejectable liquid equal to the volume of the said drop, from a temperature equal to said ambient temperature to said boiling point.

25. (Original) The system of claim 17 comprising a substrate having a substrate surface, wherein each nozzle has a nozzle aperture opening through the substrate surface, and wherein the areal density of the nozzles relative to the substrate surface exceeds 10,000 nozzles per square cm of substrate surface.

26. (Original) The system of claim 17 wherein the bubble which each heater element is configured to form is collapsible and has a point of collapse, and wherein each heater element is configured such that the point of collapse of a bubble formed thereby is spaced from that heater element.

27. (Original) The system of claim 17 comprising a structure that is formed by chemical vapor deposition (CVD), the nozzles being incorporated on the structure.

28. (Original) The system of claim 17 comprising a structure that is less than 10 microns thick, the nozzles being incorporated on the structure.

29. (Original) The system of claim 17 comprising a plurality of nozzle chambers, each corresponding to a respective nozzle, and a plurality of said heater elements being disposed within each chamber, the heater elements within each chamber being formed on different respective layers to one another.

30. (Original) The system of claim 17 wherein each heater element is formed of solid material more than 90% of which, by atomic proportion, is constituted by at least one periodic element having an atomic number below 50.

31. (Original) The system of claim 17 wherein each heater element includes solid material and is configured for a mass of less than 10 nanograms of the solid material of that heater element to be heated to a temperature above said boiling point thereby to heat said part of the bubble forming liquid to a temperature above said boiling point to cause the ejection of a said drop.

32. (Original) The system of claim 17 wherein each heater element is substantially covered by a conformal protective coating, the coating of each heater element having been

applied substantially to all sides of the heater element simultaneously such that the coating is seamless.

33. (Currently Amended) A method of ejecting a drop of an ejectable liquid from a printhead, the printhead comprising a plurality of nozzles each defining a planar ejection aperture and ~~at least one a plurality of~~ respective heater element elements corresponding to each nozzle wherein each heater element is in the form of a suspended beam having a planar structure ~~suspended between corresponding electrodes and~~ extending in a plane parallel to that of the ejection aperture, the two opposing sides of the heater element being parallel to the plane of the ejection aperture, the method comprising the steps of:

heating at least one heater element corresponding to a nozzle so as to heat at least part of a bubble forming liquid which is in thermal contact with the at least one heated heater element to a temperature above the boiling point of the bubble forming liquid;

generating a gas bubble in the bubble forming liquid by said step of heating, the bubble being generated at both of said sides of the or each heated heater element; and

causing the drop of ejectable liquid to be ejected through said corresponding nozzle by said step of generating a gas bubble,

~~wherein the heater elements and associated electrodes are arranged in each nozzle so that the electrodes are non-coincident.~~

34. (Original) The method of claim 33 comprising, before said step of heating, the steps of:

disposing the bubble forming liquid in thermal contact with the heater elements; and
disposing the ejectable liquid adjacent the nozzles.

35. (Original) The method of claim 33 wherein the bubble forming liquid and the ejectable liquid are of a common body of liquid.

36. (Currently Amended) The method of claim 33 ~~wherein each heater element is in the form of a suspended beam,~~ the step of generating a gas bubble comprising generating the gas bubble so that it surrounds the heated heater element.

37. (Cancelled)

38. (Original) The method of claim 33 wherein said step of heating at least one heater element is effected by applying an actuation energy of less than 500nJ to each such heater element.

39. (Original) The method of claim 33, comprising, prior to the step of heating at least one heater element, the step of receiving a supply of the ejectable liquid, at an ambient temperature, to the printhead, wherein the step of heating is effected by applying heat energy to each such heater element, wherein said applied heat energy is less than the energy required to heat a volume of said ejectable liquid equal to the volume of said drop, from a temperature equal to said ambient temperature to said boiling point.

40. (Previously Presented) The method of claim 33 further comprising the step of providing the printhead wherein the printhead includes a substrate on which said nozzles are disposed, the substrate having a substrate surface, and the areal density of the nozzles relative to the substrate surface exceeding 10,000 nozzles per square cm of substrate surface.

41. (Original) The method of claim 33 wherein, in the step of generating a gas bubble, the generated bubble is collapsible and has a point of collapse, and is generated such that the point of collapse is spaced from the at least one heated heater element.

42. (Original) The method of claim 33 further comprising the step of providing the printhead, including forming a structure by chemical vapor deposition (CVD), the structure incorporating the nozzles thereon.

43. (Original) The method of claim 33 further comprising the step of providing the printhead, wherein the printhead has a structure which is less than 10 microns thick and which incorporates said nozzles thereon.

44. (Original) The method of claim 33 wherein the printhead has a plurality of nozzle chambers, each chamber corresponding to a respective nozzle, the method further comprising the step of providing the printhead including forming a plurality of said heater elements in each chamber, such that the heater elements in each chamber are formed on different respective layers to one another.

45. (Original) The method of claim 33 further comprising the step of providing the printhead, wherein each heater element is formed of solid material more than 90% of which, by atomic proportion, is constituted by at least one periodic element having an atomic number below 50.

46. (Original) The method of claim 33 wherein each heater element includes solid material, and wherein the step of heating at least one heater element comprises heating a mass of less than 10 nanograms of the solid material of each such heater element to a temperature above said boiling point.

47. (Original) The method of claim 33 further comprising the step of providing the printhead, including applying to each heater element, substantially to all sides thereof simultaneously, a conformal protective coating such that the coating is seamless.